




FIRESTOP Superior 60 Drop Down Seal



Description

The FIRESTOP Superior 60 Drop Down Seals are designed to form an effective barrier against the outside climate, including noise, light, fire, smoke and insects, and are activated by the closing action of the door, meaning the seal only drops down when the door is closed. The seals are available in a variety of lengths and can be cut down to size (150mm maximum trim length). They are supplied complete with screws to ensure quick and easy fitting on either the inside or the outside of the door. The seals are acoustically tested in accordance with BS EN ISO 10140-1 & BS EN ISO 10140-2 achieving a rating of up to 48dB Rw, fire tested to BS EN 1634-1 & BS476: Part 22 to 60 minutes and smoke tested to BS EN 1634-3: 2004. It has an aluminium body and an extractable squared nylon plunger with return spring and is endurance-tested to 200,000 cycles with a 17mm maximum drop.



60 Minute Fire Rating



Complies To BS EN 1634



Complies To BS 476



Fire Tested

Features

- Suitable for timber doors
- Self-extinguishing therm type high quality co-extruded seal
- Smoke tested to BS EN 1634-3: 2004
- Fire tested to BS EN 1634-1 BS476: Part22 to 60 minutes
- Acoustically tested achieving up to 48dB Rw
- Seal activated by the closing action of the door

Product Table



L31325
1026mm



L31322
726mm



L31323
826mm



L31324
926mm