



CODELOCKS CL0610 Marine Grade Digital Lock With Tubular Latch



Description

The CL0610 and CL0615 are a marine grade heavy duty digital lock from Codelocks, suitable for both internal or external use. The outside lever handle will retract the latch after a correct code is entered, the spring loaded latchbolt will lock automatically when the door is closed.

It has been salt spray tested to 1,000 hours and comes complete with neoprene seals, ensuring it can withstand harsh outdoor environments and even coastal applications. The lock has a black finish with stainless steel buttons and is designed to suit doors with a thickness of 35mm to 60mm. There are up to 8,191 non sequential code combinations available and it features tumbler alignment for easy code change. Codelocks fire kit packs can be fitted to latch locks for 30 or 60 minute fire doors (tested in accordance with BS EN 1634 1:2008).

Clean by Codelocks is an optional finish available to special order on many Codelock products. The clear coating combats SARS-CoV-2 coronavirus (COVID-19) and can reduce bacterial growth by 99.96%*, providing an additional measure of protection over sanitisation. Clean by Codelocks features an ISO certified photocatalytic coating which offers enhanced protection against viruses, bacteria, germs and other environmental toxins. For full details please view the data sheet in the associated documents or to order please contact our Specials Department.

IMPORTANT:

Before ordering a Codelocks front/back plate set for use on an existing lock case, the current lock case must be tested to ensure it is compatible. Please see the 3rd Party Lock Disclaimer PDF document below for full information.



Supplied With 2 Keys



Key Override Facility



Reversible Handing



Weather Resistant

Features

- Large three coil lever return spring suitable for high traffic use
- Full size lever handles with return to door
- Quick Code change - no need to remove lock from door
- Specially enhanced, durable black finish suited to harsh environments
- Suitable for internal and external use
- Salt spray tested 1000 hours

Product Table



L32809

CL0610 Without Passage Set



L32810

CL0615 With Passage Set